InSuWall

Product sheet

Product description:

Application Insulating cavity walls
Insulation Polyisocyanurate (PIR) with recycled raw materials
Facing Gas-tight aluminum multi-layer coating at the top and bottom
Dimensions 1,200 x 600mm (functional 1,185 x 585mm)
Edge finishing Tongue and groove connection on all four sides

Article number	Thickness	Rd	Plates per pack	m2 per pack	Plates per pallet	m2 per pallet	Stock
301210600040	40	1,80	12	8,64	120	86,40	Yes
301210600050	50	2,25	10	7,20	100	72,00	Yes
301210600060	60	2,70	7	5,04	84	60,48	Yes
301210600070	70	3,15	6	4,32	72	51,84	Yes
301210600080	80	3,60	6	4,32	60	43,20	Yes
301210600090	90	4,05	5	3,60	50	36,00	Yes
301210600100	100	4,50	5	3,60	50	36,00	Yes
301210600110	110	5,00	4	2,88	40	28,80	Yes
301210600120	120	5,45	4	2,88	40	28,80	Yes
301210600140	140	6,35	3	2,16	36	25,92	Yes
301210600150	150	6,80	4	2,88	32	23,04	No
301210600160	160	7,25	3	2,16	30	21,60	No
301210600180	180	8,15	3	2,16	24	17,28	No
301210600200	200	9,05	2	1,44	16	11,52	No

Version 06-2025 • Changes, typographical errors and printing mistakes excepted. This version replaces all previous copies

inSus®

Roelofshoeveweg 28
6921 RG Duiven

T +31 316 – 760 900
E info@insus.nl